	CENTRAL INTELLIGENCE	GENEY BEDOUT
COUNTRY	Polani	DATE DISTR 7 December 1995
SUBJECT	Fuel Deput near Malaszewicze	NO OF PAGES 2
PLACE		25X1
CQUIRED		NO OF ENCLS
NFO.		SUPPLEMENT TO REPORT NO
	rest total	25X1
ic december as the m	INTERT TO THE RECEIPT OF AN THAN PROPERTY PRESENT	HIS IS UNEVALUATED INFORMATION
	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at	dard gauge and a Soviet gauge tation to the dump, which
2	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950.	dard gauge and a Soviet gauge tation to the dump, which Work on the construction of the
2.	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. I The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the tanks were arranged in a line from the mechanical loading and unloading of	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which work on the construction of the building, a single-story reinforced a four large tanks each with a fuel tanks, each with a capacity ware 2 or 3 meters below the decorate shell about 15 cm covered with grass and shrubbery. How the south. Connections for railroad tank cars were
2.	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. I The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the tanks were arranged in a line from the mechanical loading and unloading of available. Between July and September 1950 railroad tank cars each continuously	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which work on the construction of the building, a single-story reinforced so four large tanks each with a fuel tanks, each with a capacity ware 2 or 3 meters below the disconcrete shell about 15 cm covered with grass and shrubbery. In south, to south, Connections for railroad tank cars were 1953, trains consisting of 40 to arrived or left the installation.
	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump begen in 1950. 1 The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was the tanks were arranged in a line from the mechanical loading and unloading of available. Between July and September 1950 railroad tank cars each continuously It appeared that the depot was a fuel-trof the fuel could not be determined. A special fuel was stored and transloaded	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which work on the construction of the building, a single-story reinforced a four large tanks each with a fuel tanks, each with a capacity were 2 or 3 meters below the diconcrete shell about 15 cm covered with grass and shrubbery. However the south. Connections for railroad tank cars were 953, trains consisting of 40 to arrived or left the installation remshipping point but the origin ed at the installation.
	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. 1 The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the mechanical loading and unloading of available. Between July and September 19 50 railroad tank cars each continuously It appeared that the depot was a fuel-tr of the fuel could not be determined. A special fuel was stored and transloaded The fuel depot was directly subordinate Naftowych (Central Agency in Charge of 19 The chief of the depot was a Polish enging no military personnel appeared to be ass of the depot, but commissions including officers occasionally visited the instal	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which Work on the construction of the work on the construction of the solution of the a fuel tanks, each with a capacity ware 2 or 3 meters below the concrete shell about 15 cm covered with grass and shrubbery. For all tanks consisting of 40 to arrived or left the installation renshipping point but the origin and at the installation. To the Centrala Froduktow Petroleum Products) (CPN). Inner called Kuehn (fnu). Signed to the administration Polish Army and Air Force llation. The depot was
	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. 1 The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the mechanical loading and unloading of available. Between July and September 1950 railroad tank cars each continuously It appeared that the depot was a fuel-trof the freel could not be determined. The fuel depot was directly subordinate Naftowych (Central Agency in Charge of I The chief of the depot was a Polish engine No military personnel appeared to be assof the depot, but commissions including	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which Work on the construction of the work on the construction of the solution of the a four large tanks each with a fuel tanks, each with a capacity ware 2 or 3 meters below the deconcrete shell about 15 cm covered with grass and shrubbery. However, to south. Connections for railroad tank cars were 253, trains consisting of 40 to arrived or left the installation renshipping point but the origin and at the installation. To the Centrala Froduktow Petroleum Products) (CPN). Signed to the administration Polish Army and Air Force llation. The depot was surrounded by a double fence
	line. The distance from this railroad 1: the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. 1 The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the tanks were arranged in a line from a the mechanical loading and unloading of available. Between July and September 19 50 railroad tank cars each continuously It appeared that the depot was a fuel-to of the fuel could not be determined. The fuel depot was directly subordinate Naftowych (Central Agency in Charge of 19 The chief of the depot was a Polish enging no military personnel appeared to be ass of the depot, but commissions including officers occasionally visited the instal guarded by armed factory police and was	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which Work on the construction of the work on the construction of the soulding, a single-story reinforced a four large tanks each with a fuel tanks, each with a capacity ware 2 or 3 meters below the discovered with grass and shrubbery. Howevered with grass and shrubbery. Howevered tank cars were 2953, trains consisting of 40 to arrived or left the installation renshipping point but the origin ed at the installation. 253 to the Centrala Produktow Petroleum Products) (CPN). Inser called Kuehn (fnu). Signed to the administration Polish Army and Air Force tlation. The depot was surrounded by a double fence to the sesumption that a major
3.	the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. 1 The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the mechanical loading and unloading of available. Between July and September 1950 railroad tank cars each continuously It appeared that the depot was a fuel-troof the free could not be determined. A special fuel was stored and transloaded the chief of the depot was a Polish engine mailtany personnel appeared to be assed the depot, but commissions including officers occasionally visited the install guarded by armed factory police and was of barbed wire which was lighted at might supply base is being set up along the light CLASSIFICATION CONFIDENTIAL.	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which Work on the construction of the work on the construction of the soulding, a single-story reinforced a four large tanks each with a fuel tanks, each with a capacity ware 2 or 3 meters below the discovered with grass and shrubbery. Howevered with grass and shrubbery. Howevered tank cars were 2953, trains consisting of 40 to arrived or left the installation renshipping point but the origin ed at the installation. 253 to the Centrala Produktow Petroleum Products) (CPN). Inser called Kuehn (fnu). Signed to the administration Polish Army and Air Force tlation. The depot was surrounded by a double fence to the sesumption that a major
3.	the fuel depot was about 1.5 km. A stand spur track extended from the railroad at was also connected by road to Terespol. dump began in 1950. I The depot consisted of an administrative pumping station measuring 50 x 15 meters capacity of 300,000 liters and 16 small of 100,000 liters. All the tanks, which surface, were surrounded by a reinforced thick. The surface above the tanks was of the mechanical loading and unloading of available. Between July and September 1950 railroad tank cars each continuously It appeared that the depot was a fuel-troof the free could not be determined. A special fuel was stored and transloaded the fuel depot was a fuel-troof the free could not be determined. The fuel depot was directly subordinate Naftowych (Central Agency in Charge of I The chief of the depot was a Polish engine military personnel appeared to be assed the depot, but commissions including officers occasionally visited the install guarded by armed factory police and was of barbed wire which was lighted at might supply base is being set up along the light	ine to the northern edge of dard gauge and a Soviet gauge tation to the dump, which Work on the construction of the work on the construction of the soulding, a single-story reinforced a four large tanks each with a fuel tanks, each with a capacity ware 2 or 3 meters below the discovered with grass and shrubbery. Howevered with grass and shrubbery. Howevered tank cars were 2953, trains consisting of 40 to arrived or left the installation renshipping point but the origin ed at the installation. 253 to the Centrala Produktow Petroleum Products) (CPN). Inser called Kuehn (fnu). Signed to the administration Polish Army and Air Force tlation. The depot was surrounded by a double fence to the sesumption that a major

CONFIDENTIAL.	•		
	~2.c		
and Soviet gauge railroad railroad facilities availa improved with special stre commodities directly from	ble in this area are cont as being laid on the poss	tinuously being sibility of transleading	
<u>forment</u> . These data storage capacity of 2,300 small in view of the proba		ity appears too	25 X 1
Comment. The reporte wader civil administration the installation has a preis the case with the so-ca	dominantly military impor	ossibility that rtance just as	25 X 1
			25 X 1
		•	20/(1
			20/(1

COVERTMENTAL